



Zurich/Sihl Case Study Switzerland

WSL Swiss Federal Research Institute










Estimation of Building Department Canton Zurich; 500 years return period



- Up to 3'600 buildings affected, hundreds of special buildings
- ➤ 4-5 km² flooded area
- Material damage 4.5 bn €
- Main station damage: about 400 mn €
- Fatalities possible
- Indirect damages due to interruption of infrastructure




Estimation of Building Department Canton Zurich; 500 years return period





River Sihl crossing underneath Zurich main station





RRA methodology

➤ Flood hazard assessment

Identify flood metrics as flow velocity, water depth, flood extension

➤ Exposure assessment

Identify localisation of the receptors potentially affected by flood event


Susceptibility assessment

Evaluate degree to which receptors could be affected by flood event based on physical/environmental site-specific information

➤ Risk assessment


Define risk index that allows to identify and classify areas, receptors and hotspots at risk








Flood hazard assessment






Exposure assessment






Susceptibility assessment








Risk Classes	Number of	
(R1)	injuries	
Very low	1 - 50	
Low	50 - 100	
Medium	100 - 150	
High	150 - 200	
Very high	200 - 250	





ber of
ities




- > Total population in the study area: 290.000
- > About 1.000 injured people (0.35 %)
- ➤ About 30 fatalities (0.01%)



Receptor: infrastructures

Risk assessment



> Total length of infrastructures at risk: **210** km (55 km railways, 155 km roads/pathways (14% of total length of infrastructures within the study area)




Hazard assessment


Flood hazard threshold	Building-related risk class	Definition
v ≤ 2 or <u>v x d ≤ 3</u>	<u>Inundation</u>	Damage similar to that caused by a natural low-velocity river flood. No immediate structural damage.
v > 2 and 3 < v x d ≤ 7	Partial damage	Moderate structural damage, i.e. windows and doors knocked out. Little damage to the major structural elements of the building.
otherwise	Total destruction	Total structural collapse or major damage to the structure necessitating demolition and rebuilding.




Exposure assessment












- ➤ Buildings at risk: **3.267** (17 % of total number of buildings within the study area)
- ➤ Surface at risk: **2.2** km² (20 % of total surface covered by buildings within the study area)



Receptor: agriculture

Risk assessment




Loss of agricultural areas: 0.6 km²
 (8 % of total agricultural areas within the study area)



Receptor: cultural heritage


Risk assessment



Flooded object of historical interest: 40
 (10 % of all buildings of historical interest)




Total Risk Assessment



- High total risk index for city and main station confirms former analyses
- Other areas unexpectedly show a high total risk index

Receptor	Weight
Infrastructures	8.0
Buildings	0.6
People	0.4
Agriculture	0.2
Cultural Heritage	0.1
Natural /semi-natural systems	0









- The networks contain probability distributions
- ➤ The probability distributions are based on the evidence given by the experts
- ➤ The automated procedure is called 'learning' and is meant to train the networks so that they can reproduce the opinion of the experts
- ➤ Different exposure scenarios possible (flood day/night)
- Comparative analysis with alternative scenario based on the improvement of the Early Warning System.


















- ➤ Spatially explicit Bayesian Network
- > Flood night hit (only damage to residential people)





Outlook: Receptor infrastructures


Tram network (blue)





Outlook: Receptor infrastructures


Tram network



- Produce a network graph using the graph visualisation software Gephi, showing how all crossings are connected to each other.
- Vulnerable nodes are colored red.
- Use an R-script to produce the network under flooded conditions.

Outlook: Receptor infrastructures

Tram network



Problems Faced

- Missing velocity data
- Missing distinction between Sihl and small rivers
- > Appropriateness of resident buildings for receptor people
- Impact of 300 or 500 years return period
- Impact of water depth/velocity on buildings
- Impact of weights



